



HF-P32Q

Main Parts:

- Siemens Motor
- Schneider Electric
- Dingji Seal
- Omron Limit Switch
- Ultra high pressure silent Pump
- Argo-Hytos valve

HF-P32Q is a compact and efficient machine with either 1phase or 3 phase, designed for workshop manufacturing with hoses up to 2 inch. Compliant with ergonomic design.

Max. Hydraulic Hose	2 inch
Max. Pressure (bar)	275 bar
Crimping Range (mm)	4--87 mm
Crimping Force (kN)	2000 kN
Motor Power (kW)	4 kW
Voltage (V)	220V/ 380V
Foot pedal	Included
Die rack	Included
Quick change tool	Included
Die sets included	15 standard die sets
Dimensions (mm)	670*550*1302 mm
Total Weight (kg)	305 kg

* Special die sets are available on request

Die Sets Chart:

DieSetNo.	Crimping range	ID (mm)	L (mm)
* P32/06	6...8	6	25
* P32/08	8...10	8	25
* P32/10	10...12	10	55
* P32/12	12...14	12	55
P32/14	14...16	14	55
P32/16	16...19	16	55
P32/19	19...22	19	55
P32/22	22...26	22	70
P32/26	26...30	26	70
P32/30	30...34	30	70
P32/34	34...39	34	75
P32/39	39...45	39	75
P32/45	45...51	45	90
P32/51	51...57	51	90
P32/57	57...63	57	100
P32/63	63...69	63	100
P32/69	69...75	69	100
P32/74	74...80	74	100
P32/78	78...87	78	100

* Special die sets are available on request.